



PRODUCT DATA SHEET

PEAK LT Profiling Mastic is a petroleum based moldable compound designed to fill gaps, voids and irregular shapes prior to the application of PEAK LT Petrolatum Wax Tape.

Common uses include smoothing the irregular shapes and contours of valves, flanges bolts and any irregular shape. PEAK LT Profiling Mastic is a self-supporting compound that doesn't harden, is chemically inert and resistant to moisture.

PEAK LT PROFILING MASTIC WAX TAPE SYSTEM



FEATURES & BENEFITS

- ✓ **SIMPLE SINGLE COMPONENT COMPOUND**
Easy to apply and requires no mixing or ratio measurements.
- ✓ **PEAK LT (LOW TEMPERATURE) FLEXIBILITY**
Soft and malleable even in cold weather.
- ✓ **FLEXIBLE APPLICATION**
Can be applied underwater and to wet, dry and sweating assets.
- ✓ **EFFICIENT PREPARATION**
Minimal surface preparation SSPC SP2 – SP3.
- ✓ **INDUSTRY CERTIFIED**
Meets AWWA C217 & CSA Z245.30 system FC7 requirements.



+1-604-787-4085

info@mountain-pc.com

www.mountain-pc.com





PEAK SYSTEM

- ✓ MPC PEAK LT Petrolatum Wax Tape
- ✓ MPC PEAK LT Priming Paste
- ✓ MPC PEAK LT Profiling Mastic
- ✓ PEAK / CNRI® SynthoGlass® OUTERWRAP
- ✓ ACCESSORIES: Compression film, perforator

APPLICATIONS

- ✓ Above and below ground assets
- ✓ Valves, fittings, flanges and risers
- ✓ Soil to air transitions
- ✓ Rehab tie-ins
- ✓ Emergency repair
- ✓ Underwater and splash zones



PHYSICAL PROPERTIES

PROPERTY	SPECIFICATION
FLASH POINT	185°C (365°F)
SPECIFIC GRAVITY @ 25°C	0.605
CONE PENETRATION @ 25°C	12.5mm (0.5 in.)
DROP MELTING POINT	60°C (140°F)
MINIMUM SERVICE TEMPERATURE	-40°C (-40°F)
MAXIMUM SERVICE TEMPERATURE	50°C (122°F)

WEIGHT	BRICKS PER CASE
4kg (8.8lb)	10

SIZE & QUANTITY

ORDER PRODUCT

info@mountain-pc.com

